IP 10 Tip-On Feeder

Overview

The IP-10 Tip-On Feeder with Accuracy-Lock technology is designed for high-speed precision placement of products onto moving carrier targets. The modular design allows IP feeders to be easily integrated into existing equipment such as folder/ gluers, vacuum bases, mail tables, conveyors, flighted infeeds, tip-on systems, or configured as part of a turn-key attaching system.

Streamfeeder's Accuracy-Lock feature ensures tight placement tolerances at high speeds with one or multiple pieces per carrier. Wi-Fi enabled controls allow you to set-up and adjust the IP-10 on-the-fly from an application on your phone, tablet or laptop. Management, operators, and maintenance can view real-time diagnostics and reports allowing them to track productivity, quality and efficiencies.

Standard Features

Accuracy-Lock

adjustments

- Gum rubber feed belts
- Variable and on-the-fly Universal mount product placement
 - System I/O interface
 - Discharge guides ensures
- Servo motor/controller
- Encoder
- Vacuum assist ready
- One-knob side guide adjust

Applications - Integrates with: • Flighted Infeeds

- Folders/Gluers
- Vacuum Bases
- Mail Tables
- Conveyors

Products

- Plastic Cards
- Booklets
- Business Cards
- Coupons
- Folded Documents
- Magnets

Systems

- Pharmaceutical
- Inserts
- Promotional Items
- Sample Packs

Contact our experienced sales team today for a comprehensive review of your application/product and see how our IP-10 can benefit your company.

Hayssen | Rose Forgrove | Sandiacre | Schib | Simionato | Streamfeeder | Symach | Thiele

Streamfeeder - BW Flexible Systems 315 27th Avenue Northeast | Minneapolis, MN 55418 USA +1 (763) 502-0000 Streamfeeder.com



24" Tall Stainless Steel Side Guides One-Knob Side Guide Adjust **Durable Stainless** Patented Product Steel Construction Separator Long-Lasting Adjustable Angle Gum Rubber Discharge Feed Belts and Vacuum Assist Ready Alianment Guides Self-Adjusting Universal Discharge Mounting Kit Hold-Down

Specifications

Maximum Product Size 10" wide x 10" long (254 x 254 mm)

Minimum Product Size

2" wide x "2.5 long (51 x 64 mm)

Min/Max Product Thickness .003" to .250" (.076 to 6.35 mm)

Belt Speed

4,000 in/min (101.6 m/min)

Utilities

230vac, 1Ø, 50/60Hz, 11A

Wi-FI Enabled

Warranty

One year limited

Other sizes and thickness capabilities available.





- Adjustable discharge
- Stainless steel construction

Tip-On Systems

Turn-key Attaching



