IP-7 Tip-On Feeder

Overview

The IP-7 Tip-On Feeder with Accuracy-Lock technology is designed for high-speed precision placement of products onto moving carrier targets. The modular design allows IP feeders to be easily integrated into existing equipment such as folder/gluers, vacuum bases, mail tables, conveyors, flighted infeeds, tip-on systems, or configured as part of a turn-key attaching system.

Streamfeeder's Accuracy-Lock feature ensures tight placement tolerances at high speeds with one or multiple pieces per carrier. Wi-Fi enabled controls allow you to set-up and adjust the IP-7 on-the-fly from an application on your phone, tablet or laptop. Management, operators, and maintenance can view real-time diagnostics and reports allowing them to track productivity, quality and efficiencies.

Standard Features

- Accuracy-Lock
- Gum rubber feed belts
- variable and on-the-fly product placement • adjustments •
- Variable and on-the-fly
 Universal mount
 - System I/O interface

• Adjustable discharge

• Discharge guides ensures side-to-side registration

Self-adjusting hold-down

- Servo motor/controller
- Encoder
- Vacuum assist ready
- One-knob side guide adjust

Applications - Integrates with:

- Folders/Gluers
- Vacuum Bases
- Mail Tables
- Conveyors

Products

- Plastic Cards
- Booklets
- Business Cards
- Coupons
- Folded Documents
- Magnets
- Pharmaceutical
 Inserts
- Promotional Items
- Sample Packs
- Contact our experienced sales team today for a comprehensive review of your application/product and see how our IP-7 can benefit your company.



Streamfeeder - BW Flexible Systems 315 27th Avenue Northeast | Minneapolis, MN 55418 USA +1 (763) 502-0000 Streamfeeder.com



24" Tall Stainless Steel Side Guides One-Knob Side Guide Adjust **Durable Stainless** Patented Product Steel Construction Separator Long-Lasting Adjustable Angle Gum Rubber Discharge Feed Belts and Vacuum Assist Ready Alianment Guides Self-Adjusting Universal Discharge Mounting Kit Hold-Down

Specifications

Maximum Product Size 7" wide x 6" long (178 x 153 mm) Minimum Product Size

2" wide x "2.5 long (51 x 64 mm)

Min/Max Product Thickness .003" to .250" (.076 to 6.35 mm)

Belt Speed

4,000 in/min (101.6 m/min)

Utilities

230vac, 1Ø, 50/60Hz, 11A

Wi-FI Enabled

Warranty

One year limited

Other sizes and thickness capabilities available.



Stainless steel

construction

ow our IP-7 can benefit your company.